

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 June 2004 (17.06.2004)


PCT

(10) International Publication Number
WO 2004/050490 A1

- (51) International Patent Classification⁷: B65D 17/00, 17/34
- (21) International Application Number: PCT/SE2003/001789
- (22) International Filing Date: 18 November 2003 (18.11.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/319,749 3 December 2002 (03.12.2002) US
- (71) Applicant and
(72) Inventor: RONNBERG, Magnus [SE/SE]; Svartviksslingan 35, S-167 38 Bromma (SE).
- (74) Agents: FASTH, Rolf et al.; Fasth Law Offices, 629 E. Boca Raton Road, Phoenix, AZ 85022 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published: — with international search report

[Continued on next page]

(54) Title: METHOD FOR PROTECTING BEVERAGE CAN FROM INSECTS



(57) Abstract: The method is for preventing insects from entering an opening of a beverage can. The method provides for a beverage can (16) that has a lever member (30) with a handle member (32) and an engaging member (34) attached to a top surface (12) of the beverage can (16). A cover member (10) is placed on top of the top surface (12) so that a protection area (27) is placed above a weakened segment (36) of the top surface (12) and an inner opening segment (24) is placed below the engaging member (34). The protection area (27) has a plurality of precut segments (35). With the protecting area (27) and the segments (35) placed on top of the weakened segment (36), the handle member (32) is lifted to move the engaging member (34) through the inner opening segment (24) to push a portion of the weakened segment (36) with the segments (35) glue thereto into the beverage can (16) and creating an opening (38) that is covered by the apertures (28) of the protection area (27) to prevent insects from getting into the can (16).

BEST AVAILABLE COPY